

# 8CH POE NVR(5M Support)



## ● Key Features

- Compression Method: H.265+/H.264+
- Preview Resolution: 5M
- 1 SATA Hard Disk Interface (2.5"/3.5" SATA, Up to 8TB)
- 8CH POE Supporting, 9CH IPC Supporting Max
- Dimensions (LxWxH): 260\*215\*43(mm)

## ● Technical Specifications

Model	FX-N808POE
<b>System</b>	
Main Processor	Hi3536D
Operating System	Embedded LINUX
Video Input	8CH POE; 9CH IPC(5M/4M/3M/2M/1M, etc)
Video Output	1 VGA, 1 HD
Audio In	No
Audio Out	1 Port 3.5mm(Linear, 1kΩ)
Incoming Bandwidth	60MB
POE	8 x Independent 100Mbps PoE Network Interfaces
Motion Detection	9 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips
Email Alarm	Send Image to The Designated E-mail
<b>Display</b>	
VGA	Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HD	Resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Display Split	9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
<b>Recording</b>	
Video Compression	H265/H264/H265+/H264+
Audio Compression	G711u, G711a, ADPCM_DVI4
HDD	1 SATA Hard Disk Interface (2.5"/3.5" SATA, Up to 8TB)
Resolution	5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
Record Mode	Manual\Timer\Motion Detection\Smart Alarm
<b>Playback&amp;Network</b>	
Decode Capability	4CH 1080P@20fps
Local Sync Playback	1CH 5MP@30fps, 1CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@20fps, 4CH 960P@30fps, 4CH 720P@30fps
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS
Smart Phone	iPhone, ipad, Android ,Android pad
<b>GENERAL</b>	
Language	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian,German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 52V/2500mA ≤6W (Without Hard Disk and POE)
Working Environment	-10~55 °C /10~90%
Mouse	YES
Dimension (WxDxH)	260*215*43(mm)
Weight	2kg (Without HDD)

>>Specifications are subject to change without prior notice